




Flexible Floor Bunding

Spill Containment on Land

50mmH Low Profile Flexible Floor Bunding

Create a low-profile containment boundary that reduces trip edges and avoids disrupting day to day access while still helping keep minor spills contained. Built from heavy duty hi vis PVC with purpose extruded foam and chemical resistance.

Product Code	Description	Length	Width	Height
CHFFB39	Flexible Floor Bunding	2m	205mm	50mm
CHFFB40	90° Corner Join	300mm	205mm	50mm
CHFFB36	Installation Kit 5mL	Screws, Aluminium Flat Bar and Sealant		
CHFFB37	Installation Kit 10mL			
CHFFB08	Installation Kit 90° Corner Join	Screws		



Specifications	
Material Type	Heavy Duty Hi-Vis PVC
Material Weight	900 gsm
Chemical Resistant	Yes

Best Fit For

- Pedestrian and mixed use zones where trip risk matters more than maximum volume
- Door thresholds and access points where a taller bund would interfere with movement
- Low traffic areas needing a clear containment line near storage or light handling tasks

Not Suitable For

- Continuous forklift routes (use 75 mm instead)
- Heavy turning across the bund (wheel scrub will shorten life)
- High consequence liquids or higher volume containment requirements (use 150 mm)

DISCLAIMER: Chatoyer is not responsible for any product malfunctions, damage, or performance issues resulting from misuse, unauthorised modifications, improper installation, external environmental factors, or failure to follow recommended usage guidelines. This includes, but is not limited to, damage caused by accidents, natural disasters, power surges, or use with incompatible accessories. All warranties and support services apply only to products used in accordance with the manufacturer's instructions and within the intended operating conditions.



CHATOYER

WWW.CHATOYER.COM.AU | 1300 880 623

NSW 351 Wentworth Avenue, Pendle Hill, NSW 2145 QLD 2/27 Service St Maroochydore QLD 4558

VERSION 280125