



# Urethane Floor Bunding

Spill Containment on Land

## EASY TO INSTALL, VERSATILE AND DURABLE FLOOR BUNDING

Urethane Floor Bunding is flexible, durable, and UV stabilised. Ideal for bunding around tanks, drums, and doorways. Offers chemical resistance and high visibility. Pre-drilled lengths and corners allow quick installation. Low profile minimises trip hazards and allows forklift access. For high traffic or permanent use, aluminium bunding is recommended.

Product Code	Description	Length	Width	Height
CHUFB05	Urethane Floor Bunding Predrilled with 6 screw anchors (8mm x 60mm)	1m	150mm	25mm
CHUFB06	Urethane 90° Corner Predrilled with 4 screw anchors (8mm x 60mm)	200mm	200mm	25mm
CHGA01	Sikaflex 11FC Grey 310ml			

Specifications	
Material Type	UV-stabilised urethane
Visibility	HiVis yellow
Height	Low profile (forklift-friendly)
UV Resistant	Yes



## APPLICATION

- Warehouse
- Liquid storage areas
- Workshops
- Factories
- Filling Stations

**DISCLAIMER:** Chatoyer is not responsible for any product malfunctions, damage, or performance issues resulting from misuse, unauthorised modifications, improper installation, external environmental factors, or failure to follow recommended usage guidelines. This includes, but is not limited to, damage caused by accidents, natural disasters, power surges, or use with incompatible accessories. All warranties and support services apply only to products used in accordance with the manufacturer's instructions and within the intended operating conditions.



# CHATOYER

WWW.CHATOYER.COM.AU | 1300 880 623

NSW 351 Wentworth Avenue, Pendle Hill, NSW 2145 QLD 2/27 Service St Maroochydore QLD 4558

VERSION 170725