

The SpilMax® range of absorbents have undergone extensive testing to ensure their absorbency and performance.

SpilMax® Oil & Fuel Absorbent Rolls will absorb a wide variety of plant and seed oils, hydrocarbons, petrochemicals and petroleum-based solvents. Because the pads are hydrophobic and repel water, they are an ideal absorbent for use around water and in wet conditions.

Even when fully saturated, these pads will float on water. They are ideal for use with

spills in waterways, and for use on boats, in marinas, on wet worksites and in or near stormwater outlets.

Rolls of perforated pads will tear off in custom sized sheets ideal for use under vehicles and equipment during maintenance or refueling and to create set down areas for containers or leaking equipment. Single pads can be used to capture small leaks, clean up small spills and wipe down tools, equipment or drum tops.

Made of melt blown polypropylene with dimples and scrim for greater durability. Each pad absorbs 1L per saturation. Pads can be wrung out and reused many times during spill clean up.

**TESTING:** ASTM Test Method F726-06 "Sorberent Performance of Absorbents" to test maximum oil capacity.



CODE	GSM	SIZE	DIMENSIONS	WEIGHT
CH1308	400gsm	43mL x 960mmW Full Roll	0.48mL x 0.48mW x 0.96mH	15 kg
CH13083	400gsm	43mL x 480mmW Half Roll	0.48mL x 0.48mW x 0.48mH	8 kg
CH1307	200gsm	43mL x 960mmW Full Roll	0.35mL x 0.35mW x 0.96mH	8 kg
CH13073	200gsm	43mL x 480mmW Half Roll	0.35mL x 0.35mW x 0.48mH	4 kg